

Serial No.: 10/625,542

IN THE CLAIMS:

1.-16. (Cancelled)

17. (Currently Amended) A disk device ~~with a disk arranged inside a frame body, wherein~~ comprising:

a frame body having an outer wall;

a recording disk located for rotation inside the frame body; and

a recording and reproducing head; wherein

~~said disk device includes an actuator for driving a~~ the head for recording and reproducing information on and from the disk,

said actuator ~~is composed of~~ comprises a voice coil motor comprising a pair of yokes opposed to each other with a predetermined distance therebetween, a movable coil wound to be movable between the yokes, and a permanent magnet attached to at least one of the yokes to add a magnetic field to the movable coil, ~~and~~

Serial No.: 10/625,542

~~one of the yokes forms a part of an outer wall of the frame body, in place of the frame body.~~ a portion of said outer wall of said frame body comprises a first one of said yokes, and
said frame body comprises an open side opposite a side where said disk is located and an inside portion comprising screwing margins and screws for attaching said first yoke to said open side.

18.-19. (Cancelled)

20. (Currently Amended) A disk device as set forth in Claim 1917, wherein said first yoke comprises concave portions ~~are formed on the yoke for~~ embedding therein head portions of the screws.

21. (Currently Amended) A disk device as set forth in Claim 20, ~~wherein electric components are arranged in a space created by embedding the head portions of the screws~~ further comprising electronic components, wherein said embedded head portions of the screws do not extend beyond a surface of said

Serial No.: 10/625,542

first yoke, and said electronic components are located adjacent
said surface of said first yoke.

22.-23. (Cancelled)

24. (Currently Amended) A disk device as set forth in
Claim 2317, wherein further comprising a sheet comprising an
adhesive portion and having a hole therein, wherein: the sheet
~~has a hole, and~~

a part of the first yoke forming, in place of the frame
~~body, a part of the outer wall of the frame body penetrates~~
through is located in the hole, and

a gap is located between the frame body and a rim of the
yoke, said gap being in the outer wall of the frame body, and
shielded by said sheet.

25. (Cancelled)

Serial No.: 10/625,542

26. (Currently Amended) A disk device as set forth in Claim 2217, ~~wherein electric components are arranged in a space created by the thinly formed part of the yoke wherein a first~~ part of said first yoke has a first thickness except at a second part corresponding to a central portion of the permanent magnet which has a second thickness, the first thickness being thinner than the second thickness, and said disk device further comprises electronic components located adjacent said first part.

27.-30. (Cancelled)